

Compatibility, System Requirements, Hardware Specifications

SYSTEM REQUIREMENTS

Windows® XP (latest Service Pack, 32 Bit) or **Windows Vista®** (latest Service Pack, 32/64 Bit) or **Windows® 7** (latest Service Pack, 32/64 Bit), Intel® Pentium 4® or Intel® Core™ or AMD Athlon™ 64, 2 GB RAM

Mac OS® X 10.5 (latest update) or 10.6 (latest update), Intel® Core™ Duo, 2 GB RAM

SUPPORTED DRIVERS

- ASIO®
- Core Audio
- DirectSound®
- WASAPI

DIMENSIONS

26 x 59 x 91 mm / 1.0 x 2.3 x 3.6"
Weight: 84g / 0,19 lbs

POWER SUPPLY

Power Supply Via USB 2.0 interface, 5V 500mA bus power. No additional power supply or battery is needed.

HARDWARE SPECIFICATIONS

Audio Converters (Inputs A/D)	
Channels (A/D, D/A)	0, 4
Sample Rates	44.1, 48, 88.2, 96 kHz
Bit Resolution	24 Bit
Converter	Cirrus Logic
Line Outputs	
Max. Output Level	+9.6 dBu
Gain	
Dynamic Range (A weighted)	101 dBu (A)
THD+N (Max. Level)	0.007%
Frequency Response, -1 dB	10 Hz - 40 kHz
Cross Talk @ 1 kHz to next channel	-87 dBu
Headphone Output	
Load Impedance	8 Ohms - 600 Ohms
Maximum Output Level	9.3 dBu, 4.26 V rms, 100 mW @ 100 Ohms
Dynamic Range (A weighted)	95 dBu
THD+N (Max Level, high Imp, 100 Ohms)	0.012%
Frequency Response (96 kHz), -1 dB	10 Hz - 40 kHz