

# POWERCORE COMPACT



FireWire  
connections

Power  
Input

## POWERCORE COMPACT SYSTEM REQUIREMENTS

### MAC OS

Laptop/desktop, G4/G5/Intel, 1 GHz or better

512 MB RAM or more

Mac OS X (10.4 or higher)

One available Firewire port (400 Mbit IEEE 1394)

17" color monitor (resolution 1024 x 768) or higher recommended.

Any VST or AudioUnits compatible recording software

(Cubase SX, Logic, Nuendo, Bias Peak, Live, Digital Performer), Pro Tools with FXpansion VST-RTAS wrapper (optional)

Any sound system supported by the host application

60 Megabytes of available hard disk space

Internet Connection for product registration

### WINDOWS

Laptop, Pentium 4, 1.4 GHz or better

512 MB RAM or more

One available Firewire port (400 Mbit IEEE 1394)

Windows XP

17" color monitor (resolution 1024x768) or higher recommended.

Any VST-compatible application (Cubase, WaveLab, Nuendo, Samplitude, Sonar,

Live and Pro Tools with Expansion VST-RTAS wrapper (optional)

Any audio interface supported by the host application

60 Mb of available hard disk space

Internet connection for product registration

## POWERCORE COMPACT SPECIFICATIONS

2 x Motorola 56367 DSP / 150 MHz

512 k Word SRAM per DSP

1x 266 MHz Motorola 8245 PowerPC

8 MB SDRAM on board.

Power Requirements typically lower 10 W. Peak max. 20 W.

Operating temperature: 0° C – 40° C (32° F – 104° F)

Storage temperature: -30° C – 80° C (-22° F – 176° F)

Humidity: max. 90%, non-condensing

### Included Plug-Ins:

24/7C

Character™

Chorus-Delay

ClassicVerb

EQsat Custom

Filteroid

MasterX3

MegaReverb

PowerCore 01

Tubifex

Vintage CL

VoiceStrip