


POWERCORE EXPRESS



PCI Express
connections

| POWERCORE POWERCORE EXPRESS SYSTEM REQUIREMENTS | POWERCORE EXPRESS SPECIFICATIONS |
|--|---|
| <p>MAC OS Laptop/desktop, G4/G5/Intel, 1 GHz or better 512 MB RAM or more Mac OS X (10.4 or higher) One free PCI Express (PCIe) slot 17" color monitor (resolution 1024 x 768) or higher recommended. Any VST or AudioUnits compatible recording software (Cubase SX, Logic, Nuendo, Bias Peak, Live, Digital Performer), Pro Tools with FXpansion VST Any sound system supported by the host application Mouse or other pointing device 60 Megabytes of available hard disk space Internet Connection for product registration</p> | <p>POWERCORE EXPRESS SPECIFICATIONS</p> <p>4 x Motorola 56367 DSP / 150 MHz 512 k Word SRAM per DSP 1x 266 MHz Motorola 8245 PowerPC 8 MB SDRAM on board.</p> <p>Operating temperature: 0° C – 40° C (32° F – 104° F) Storage temperature: -30° C – 80° C (-22° F – 176° F) Humidity: max. 90%, non-condensing</p> |
| <p>WINDOWS Pentium 4, 1.4 GHz or better 512 MB RAM or more One free PCI Express (PCIe) slot Windows XP 17" color monitor (resolution 1024x768) or higher recommended. Any VST-compatible application (Cubase, WaveLab, Nuendo, Samplitude, Sonar, Live and RTAS/Pro Tools with Xpansion VST-RTAS wrapper (optional) 60 Mb of available hard disk space Internet connection for product registration</p> | <p>INCLUDED PLUG-INS IN POWERCORE EXPRESS</p> <p>24/7-C Character™ Chorus-Delay ClassicVerb EQsat Custom Filtroid MasterX3 MegaReverb PowerCore 01 Tubifex Vintage CL VoiceStrip Dynamic EQ DeNoise</p> |